



# BF1000

## Brake Fluid

BF1000 is a glycol based, DOT 3 brake fluid.

BF1000 meets or exceeds FMVSS 116, SAE J1703, and ISO 4925 standard requirements.

Packaging is available in 55 gallon drums, totes, or bulk delivery.

### Product information

Colour

Amber<sup>[1]</sup>

[1]: Clear to Light Amber

### Rheological properties

Kinematic viscosity, -40°C

1140 mm<sup>2</sup>/s

FMVSS 116

Kinematic viscosity, 100°C

2.1 mm<sup>2</sup>/s

FMVSS 116

### Thermal properties

Flash point

135 °C

ASTM D 92

Equilibrium Reflux Boil Point, as produced

262 °C

FMVSS 116

Equilibrium Reflux Boil Point, humidified

149 °C

FMVSS 116

### Other properties

Specific Gravity

1.02

ASTM D 4052

pH

9.5

Revised: 2021-02-04

Page: 1 of 1

### DuPont

The information set forth herein is furnished free of charge, is based on technical data that DuPont believes to be reliable, and represents typical values that fall within the normal range of properties. This information relates only to the specific material designated and may not be valid for such material used in combination with other materials or in other processes. It is intended for use by persons having technical skill, at their own discretion and risk. This information should not be used to establish specification limits nor used alone as the basis of design. Handling precaution information is given with the understanding that those using it will satisfy themselves that their particular conditions of use present no health or safety hazards and comply with applicable law. Since conditions of product use and disposal are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information. As with any product, evaluation under end-use conditions prior to specification is essential. Nothing herein is to be taken as a license to operate or a recommendation to infringe on patents.

CAUTION: Do not use DuPont materials in medical applications involving implantation in the human body or contact with internal body fluids or tissues unless the material has been provided from DuPont under a written contract or other acknowledgement that is consistent with the DuPont policy regarding medical applications and expressly acknowledges the contemplated use. For further information, please contact your DuPont representative.

DuPont's sole warranty is that our products will meet our standard sales specifications in effect at the time of shipment. Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted. TO THE FULLEST EXTENT PERMITTED BY APPLICABLE LAW, DUPONT SPECIFICALLY DISCLAIMS ANY OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, OR NON-INFRINGEMENT. DUPONT DISCLAIMS LIABILITY FOR ANY SPECIAL, INCIDENTAL, OR CONSEQUENTIAL DAMAGES.

DuPont™, the DuPont Oval Logo, and all trademarks and service marks denoted with ™, SM or ® are owned by affiliates of DuPont de Nemours, Inc. unless otherwise noted.

© 2022 DuPont. All rights reserved.